



# GOLDTRUST SUPER SYN 0W/20

Goldtrust Super Syn 0W/20 is a Fully Synthetic oil developed with robust additive technology to give excellent engine protection and performance characteristics. It provides exceptional protection against wear and overall performance as well as overperforms other conventional oils.

Goldtrust super Syn 0W/20 helps extended engine life by minimizing wear & maintaining the engine free of harmful deposits, delivers extended drain intervals and protects emission control systems.

## APPLICATION

- GoldTrust Super is suitable for use where 0W-20 is recommended for use
- All Asian OEMs engine design
- TGD engines
- PFI engines
- Suitable for use under a wide range of temperature conditions.

## PERFORMANCE SPECIFICATIONS

- API: SN/CJ4
- ILSAC GF-6A (backward compatible to ILSAC GF-5),
- Ford WSS-M2C962-A1 (backward compatible with Ford WSS-M2C947-B1).
- Goldtrust Super syn 0W/20 meets or exceeds the requirement of various vehicle manufactures

## BENEFITS

- Good for modern efficiency turbocharged gasoline engine.
- Easy flow in cold weather for quick start up
- Reduce oil aging
- Excellent lubrication and wear protection

## TYPICAL CHARACTERISTICS

TEST	UNITS	ASTM TEST METHOD	RESULTS
SAE GRADE	-	-	SYN 0W/20
Appearance			C&B
Kinematic Viscosity@40°C	mm <sup>2</sup> /s	D445	39.81
Kinematic Viscosity@100°C	mm <sup>2</sup> /s	D445	7.70
Viscosity Index		D2270	166
Density@15°C	Kg/m <sup>3</sup>	D1298	0.8605
Pour Point	°C	D97	-41
Flash point	°C	D92	225
TBN	Mg/KOH/g	D2897	9.12
Sulphated Ash	%	D874	0.84

\*\*\*Some variations in Product typical characteristics should be expected during manufacturing.

PACK SIZE: 1Litre,4Litres and 5Litres

Health and Safety: This Product is not classified as hazardous under E.C Dangerous substance preparation Directives. It does not require any special care other than the normal practice for handling petroleum products