



TRUST 2 STROKE ENGINE OIL

Trust 2 stroke engine is a specially formulated, self-mixing 2-stroke engine oil having low ash-forming properties to prevent plug fouling and ring sticking.

APPLICATION

Trust 2-Stroke engine is suitable for:

- All motorcycles, mopeds and scooters
- Chain saws
- Lawn mowers
- Generator that are lubricated either by auto- lube system or petrol mixture.

PERFORMANCE/SPECIFICATION

- API: TC
- ISO: L-GED
- JASO: FD

BENEFITS:

- Reduces oil consumption
- Low exhaust smoke
- Excellent corrosion and protection properties
- Good thermal and oxidation stability and deposit control
- Perfectly adapted to unleaded fuel

TYPICAL CHARACTERISTICS

TEST	UNITS	ASTM TEST METHOD	RESULTS
SAE GRADE	-	-	30(2 Stroke Engine oil)
Appearance	-	-	C&B
Kinematic Viscosity@40°C	mm ² /s	D445	77.75
Kinematic Viscosity@100°C	mm ² /s	D445	9.3
Viscosity Index		D2270	95
Density@15°C	Kg/m ³	D1298	0.880
Pour Point	°C	D97	-27
Flash point	°C	D92	230
Sulphated ash	%	D874	0.05

****Some variations in product typical characteristics should be expected during manufacturing*

PACK SIZE: 1Litre, 205LITRES AND BULK

HEALTH & SAFETY: This product is not classified as hazardous under the E C Dangerous Substances and preparations directives. It does not require any special care other than the normal practices for handling petroleum products.