



TRUST AC (COMPRESSOR OIL)

TRUST AC series are Compressor oils formulated from high quality mineral base stocks and advanced additive technology which has good protection and performance that deliver reliable protection for rotary sliding vane and screw air compressors. All grades are treated with anti – oxidant, anti-rust and anti- wear additives.

APPLICATION

- Trust AC is recommended for lubricating both the cylinders and crankcase of reciprocating air compressors.
- Useful for rotary vane, screw and centrifugal compressors.
- For hydraulics and Turbine systems requiring a low pressure R&O Type oil

PERFORMANCE/SPECIFICATIONS

- DIN: 51506 VDL
- ISO: L-DAB
- ISO: L-DAG

BENEFITS

- Minimized Engine deposits.
- Optimum wear protection to extend engine efficiency and service life
- Neutralization of corrosive acids
- Good oxidation and thermal stability reduce sludge build up and keeps the engine cleaner.
- Improved fuel economy, due to high fluidity at low temperature.

TYPICAL CHARACTERISTICS

TEST	UNITS	ASTM TEST METHOD	RESULT			
			32	46	68	100
ISO GRADE	-	-	32	46	68	100
Appearance			C&B	C&B	C&B	C&B
Kinematic Viscosity@40°C	mm ² /s	D445	32.2	46.2	68.5	100
Kinematic Viscosity@100°C	mm ² /s	D445	5.4	6.79	8.60	11.2
Viscosity Index		D2270	102	100	98	97
Density@15°C	Kg/m ³	D1298	0.873	0.882	0.884	0.887
Pour Point	°C	D97	-40	-35	-30	-29
Flash point	°C	D92	220	232	240	248
Total Acid no	Mg/KOH/g	D664	0.09	0.09	0.09	0.09

****Some variations in Product typical characteristics should be expected during manufacturing.*

PACK SIZE: 25Litres, 205Litre and Bulk

HEALTH & SAFETY: This product is not classified as hazardous under E.C Dangerous substances and Dangerous preparations directives. It does not require any special care other than the normal practices for handling petroleum products.