



AUTOMATIC TRANSMISSION FLUID ATF11G (MULTIFUNCTION FLUID)

Trust Automatic Transmission Fluid (ATF) is a high-performance fluid for all General Motors and Ford automatic transmissions requiring DETRON®111G or MERCON® quality fluids respectively. It was formulated using a specially selected performance additives and base oils to improve thermo-oxidative stability, friction retention properties, corrosion and rust protection.

APPLICATION

- Trust AFT III G is suitable for automatic transmission requiring General Motors, DEXTRON® 11E or DEXTRON 11®11D Fluids
- Recommended for power steering systems, hydraulic applications and certain manual transmissions where applicable.

PERFORMANCE/SPECIFICATION

- GM: DEXON III G
- ALLISON: C-4
- CAT: TO-2
- FD: MERCON
- ALLISON: TES -389
- MB: 236.1/236.

BENEFITS

- Outstanding thermo-oxidation and heat stability, wear protection and resistance against degradation at high operating temperatures.
- Excellent friction property providing smooth transmission and good shift performance.
- Better protection against rust and corrosion.
- Excellent anti-foaming ability ensuring effective transfer of power
- Outstanding fluidity at low temperature pumpability and circulation ensures good cold start performance.
- Compatibility with all common seal materials reduces possibility of oil leakage.

TYPICAL CHARACTERISTICS

TEST	UNITS	ASTM TEST METHOD	RESULTS
SAE GRADE	-	-	ATF111G
Appearance	-	-	C&B
Kinematic Viscosity@40°C	mm ² /s	D445	39.3
Kinematic Viscosity@100°C	mm ² /s	D445	7.1
Viscosity Index		D2270	145
Density@15°C	Kg/m ³	D1298	0.876
Pour Point	°C	D97	-40
Flash point	°C	D92	220

****Some variations in Product typical characteristics should be expected during manufacturing*

PACK SIZE: 25Litres, 205Litre and Bulk

HEALTH & SAFETY: This product is not classified as hazardous under E.C Dangerous substances and Dangerous preparations directives. It does not require any special care other than the normal practices for handling petroleum products.