

TRUST G

GAS ENGINE OIL

TRUST G is a heavy-duty lubricating oil, developed mainly for highly rated modern engines using biogas or landfill gas as a fuel. This engine oil, formulated with high-quality, high Viscosity Index base oils and a special additives package, provides optimum control of deposits in severe conditions and protection against wear, rust and corrosion at high or low temperatures

APPLICATION

-Trust G is specially designed for gas engines used primarily for electricity generation, operating under heavy loads and harsh conditions

PERFORMANCE/ SPECIFICATIONS

- API: CF

Trust G Is approved for:

- Jenbacher Fuel Class B (Biogas) and C (Landfill),
- Engines Type II and III all versions; Type IV version AB; Type VI up to version E.

BENEFITS

- Long service life
- Good detergency secures clean engine components
- Good resistance against nitration
- Protects against valve seat recession
- Good acid neutralizing capacities
- Minimizes ring scuffing
- Control high temperature deposits due to excellent solvency properties

TYPICAL CHARACTERISTICS:

TEST	UNITS	ASTM TEST METHOD	RESULTS
SAE GRADE	-	-	G 40
Appearance			C&B
Kinematic Viscosity@40°C	mm ² /s	D445	156
Kinematic Viscosity@100°C	mm ² /s	D445	15.5
Viscosity Index		D2270	101
Density@15°C	Kg/m ³	D1298	0.885
Pour Point	°C	D97	-18
Flash point	°C	D92	245
TBN	Mg/KOH/g	D2897	7.0
Sulphated Ash	%	D874	0.6

***Some variations in Product typical characteristics should be expected during manufacturing

PACK SIZE: 205Litre and Bulk

HEALTH & SAFETY: This product is not classified as hazardous under E.C Dangerous substances and Dangerous preparations directives. It does not require any special care other than the normal practices for handling petroleum products.