



TRUST GREASE (MULTIPURPOSE GREASE)

TRUST Multi – purpose grease is a lithium -based grease formulated with a lithium soap thickener and high-quality refined mineral oil. It contains rust and oxidation inhibitors to ensure excellent performance and long life. Available in NLGI grades 1, 2 and 3.

APPLICATION

Trust Multipurpose grease can be:

- Uses as a general purpose automotive and chassis applications
- Used in machine tool applications
- Used in industrial antifriction and plain bearings
- Used For Lubricating rolling and sliding bearings.
- Operated within a temperature of -15°C - 140°C

PERFORMANCE/ SPECIFICATIONS

- NLGI: 1,2 and 3
- GB : 7324-98

BENEFITS

- Contains water repellent additives-
- Prevention of seizure particularly under aqueous condition.
- Exceptional dimensional stability and mechanical strength.
- Good oxidation resistance.
- Lithium-soap thickener ensures good mechanical stability

TYPICAL CHARACTERISTICS

TEST	UNITS	ASTM TEST METHOD	RESULTS		
			EP1	EP2	EP3
GRADE OF CONSISTENCY NLGI	-	-	EP1	EP2	EP3
Texture			Smooth	Smooth	Smooth
Kinematic Viscosity@40°C	mm ² /s	D445	37	103.8	149.5
Penetration@60 Strokes	°C	D-217	324	285	230
Penetration@100,000strokes	°C	D-217	309	296	257
Mechanical Stability@25°C	°C		110	98	100
Dropping Point	°C	D-2265	194	194	193
Oil separation 24@100°C	°C	D-6184	9.7	1.5	0.0
Water Wash out@79°C	°C	D-1264	2	2	1

****Some variations in Product typical characteristics should be expected during manufacturing.*

PACK SIZE: 1Kg, 25Kg and 205Kg

HEALTH & SAFETY: This product is not classified as hazardous under E.C Dangerous substances and Dangerous preparations directives, It does not requires any special care other than the normal practices for handling petroleum products.