



TRUST HD (Premium Monograde Diesel Engine Oil)

TRUST HD is heavy duty monograde diesel engine oil formulated with high quality solvent refined paraffinic base oil with balanced additives packaged to meet the lubrication requirement of modern diesel used in on- road and off-road applications. The high- performance additives used in Trust HD is designed to provide require performance in the area of detergency, dispersancy, wear protection and protection against bearing corrosion.

APPLICATION

-Trust HD oil is suitable for diesel, LPG and natural gas engines requiring API service CD or CD II types of oils.

-The SAE 40 grade is specifically recommended for oil bath air cleaner, chain drives, hydraulic systems of mobile equipment

PERFORMANCE/SPECIFICATION

API: CD/SF

US MILL: L2104D

ALLISON: C-4

CATER:TO2

BENEFITS

- Very good detergent additive for cleaning engine
- Good resistance to oxidation and bearing corrosion
- Excellent anti wear and anti- corrosion performance against wearing and corrosion of the engine.

TYPICAL CHARACTERISTICS

TEST	UNITS	ASTM TEST METHOD	RESULTS			
			10W	30	40	50
SAE GRADE	-	-	10W	30	40	50
Appearance			C&B	C&B	C&B	C&B
Kinematic Viscosity@40°C	mm ² /s	D445	44.0	102.5	158.05	232.6
Kinematic Viscosity@100°C	mm ² /s	D445	6.8	11.5	15.30	19.5
Viscosity Index		D2270	110	100	98	96
Density@15°C	Kg/m ³	D1298	0.875	0.880	0.885	0.895
Pour Point	°C	D97	-25	-18	-12	-11
Flash point	°C	D92	210	225	240	260
TBN	Mg/KOH/g	D2897	5.5	5.5	5.5	5.5
Sulphated Ash	%	D874	0.9	0.9	0.9	0.9

****Some variations in Product typical characteristics should be expected during manufacturing.*

PACK SIZE: 1Litre, 4Litre,25Litres, 205Litre and Bulk

HEALTH & SAFETY: This product is not classified as hazardous under E.C Dangerous substances and Dangerous preparations directives. It does not require any special care other than the normal practices for handling petroleum products.