



TRUST ROCK DRILL OIL

Trust rock drill oils are specifically formulated with selected highly refined mineral base stock with advanced technology extreme pressure additive. It is recommended for most machinery lubricated by means of oil circulation systems,

APPLICATION

- They are recommended for use in pneumatic equipment including jackhammers, pavement breakers, stoppers and drifters
- Suitable to be used in industrial gearboxes that require gear oil.
- Suitable for machinery of small steel components having a high machinability index.
- Most viscous grades are suitable for bearings, crank mechanisms and gears of heavier machines.

PERFORMANCE/SPECIFICATIONS

- AGMA 9005-EO2
- DIN 51517 P3
- ISO 12925-1 CKD
- FLENDER MICROPITTING

BENEFITS

- Good lubrication and cooling properties
- Excellent emulsifying properties
- Excellent extreme pressure and anti-wear performance
- Good Rust and corrosion inhibitors protect metal parts

TYPICAL CHARACTERISTICS

TEST	UNITS	ASTM TEST METHOD	RESULT					
			100	150	220	320	460	680
ISO GRADE	-	-	100	150	220	320	460	680
Appearance			C&B	C&B	C&B	C&B	C&B	C&B
Kinematic Viscosity@40°C	mm ² /s	D445	103.35	148.65	215.89	306.1	430.45	641.6
Kinematic Viscosity@100°C	mm ² /s	D445	11.4	14.5	18.44	24.3	33.6	45.6
Viscosity Index		D2270	97	96	95	101	115	120
Density@15°C	Kg/m ³	D1298	0.880	0.885	0.895	0.901	0.905	0.916
Pour Point	°C	D97	-24	-20	-16	-14	-9	-9
Flash point	°C	D92	235	240	249	250	258	265
Phosphorus	%	D1019	0.016	0.016	0.016	0.016	0.016	0.016

***Some variations in Product typical characteristics should be expected during manufacturing.

PACK SIZE: 25LITRES, 205LITRES AND BULK

HEALTH & SAFETY: This product is not classified as hazardous under the E C Dangerous Substances and preparations directives. It does not require any special care other than the normal practices for handling petroleum products.