



TRUST SUPER 6000 20W/50

TRUST 6000 20/W50 is designed with high quality base stocks and advanced additive technology which provides strong level of protection and performance. It works better than other conventional motor oils by continuously preventing dirt and sludge build up and reduces engine noise.

APPLICATION

- Trust 6000 for passenger cars, SUV, light trucks and vans.
- It is also suitable for naturally aspirated or turbo charged engines
- Suitable for use under a wide range of temperature conditions.

PERFORMANCE SPECIFICATIONS

- API: SL/CF
- ACEA: A3/B3/B4/E2
- MB APPROVAL: 229.1
- MTU DDC: Type-2

BENEFITS

- Good Dispersency and detergency properties.
- Excellent Anti foam properties and ensuring oil supply easily.
- Good protection against rust, corrosion and wear
- Help minimize oil Consumption

TYPICAL CHARACTERISTICS

TEST	UNITS	ASTM TEST METHOD	RESULTS
SAE GRADE	-	-	20W/50
Appearance			C&B
Kinematic Viscosity@40°C	mm ² /s	D445	159.7
Kinematic Viscosity@100°C	mm ² /s	D445	18.5
Viscosity Index		D2270	130
Density@15°C	Kg/m ³	D1298	0.887
Pour Point	°C	D97	-24
Flash point	°C	D92	230
TBN	Mg/KOH/g	D2897	8.50
Sulphated Ash	%	D874	1.2

***Some variations in Product typical characteristics should be expected during manufacturing.

PACK SIZE: 1Litre,4Litres,5Litres, 25Litres ,205Litres AND BULK

Health and Safety: This Product is not classified as hazardous under E.C Dangerous substance preparation Directives. It does not require any special care other than the normal practice for handling petroleum products

