





TRUST Surett N5K is an Open Gear grease formulated with a high viscosity mineral oil in a non-soap based thickener typically used in a chain and open gear lubricant applications.

APPLICATION

- Trust Surett is suitable for initial lubrication of chains with hollow equipped with grease nipples.
- Also used for gear drives and open gears, sliding bearings operating at low speed and high temperatures PERFORMANCE/SPECIFICATION

• DIN: 51350 PT4 • DIN: 51350 P

BENEFITS

- Emergency Lubrication
- High Pressure resistance
- High wear Protection
- Extreme adhesive
- Resistance Against water

TYPICAL CHARACTERISTICS:

TEST	UNITS	ASTM TEST METHOD	RESULTS
PRODUCT NUMBER	-	-	SURETT N5K
Colour	-	-	Brown-Black
Resultant Film	-	-	Tacky
Texture	-	-	Smooth
Thickener Type	-	-	Inorganic Clay
Kinematic Viscosity@40°C	mm²/s	D445	6532
Kinematic Viscosity@100°C	mm²/s	D445	152
Penetration, @25°C	°C	D217	270
Time OK Load,ib	Per/s		40
Flash point	°C	D92	204
Rust Test	%	D1743	Pass

^{***}Some variations in Product typical characteristics should be expected during manufacturing

PACK SIZE: 25Litres, 205Litre and Bulk

HEALTH & SAFETY: This product is not classified as hazardous under E.C Dangerous substances and Dangerous preparations directives. It does not require any special care other than the normal practice for handling petroleum products.