



TRUST XD (PREMIUM MULTIGRADE DIESEL ENGINE OIL)

TRUST XD Multigrade is a high performance, heavy duty, mixed fleet automotive engine oil. It is formulated for use in a wide range of Japanese and European diesel engines requiring API CH-4 performance, both naturally aspirated and turbo charged. It can be used in petrol engines where an SAE 15W40 and API SL lubricant is called for.

APPLICATION

- Trust XD oils are suitable for use in both turbo charged and naturally aspirated diesel engines.
- Meet the requirements of latest design and high -performance diesel engines.
- It can be used on power shift transmission and mobile hydraulic system where 15W/40 CH4 is Specified 3/BE

PERFORMANCE/SPECIFICATION

- API: CH-4/SL
- ALLISON: C-4
- MACK: EO-M PLUS
- FORD: M2C-1-53E
- ACLEA: A3B3E3ES
- MB: 228.3, 229.1
- ACEA: A3/BE7E2

BENEFITS:

- Outstanding detergent-dispersant properties for cleaner and healthier engine.
- Excellent anti-oxidation and anti-acidification abilities effectively prolonging oil drain interval
- Excellent TBN retention and good anti corrosion ability.
- Very good Viscosity stability for steady performance.
- Suitable for engines using fuels with different sulphur content

TYPICAL CHARACTERISTICS

TEST	UNITS	ASTM TEST METHOD	RESULTS
SAE GRADE	-	-	15W/40 – CH4/SL
Appearance			C&B
Kinematic Viscosity@40°C	mm ² /s	D445	120.5
Kinematic Viscosity@100°C	mm ² /s	D445	14.90
Viscosity Index		D2270	130
Density@15°C	Kg/m ³	D1298	0.887
Pour Point	°C	D97	-27
Flash point	°C	D92	228
TBN	Mg/KOH/g	D2897	11.5
Sulphated Ash	%	D874	1.3

***Some variations in Product typical characteristics should be expected during manufacturing

PACK SIZE: 25Litres, 205Litre and Bulk

HEALTH & SAFETY: This product is not classified as hazardous under E.C Dangerous substances and Dangerous preparations directives. It does not require any special care other than the normal practices for handling petroleum products.